

## Drywall and Thin Coat Beads

Galvanised beads for internal thin-coat plaster application.

### Locusrite Perforated Thin Coat Bead

#### Description and Application

Available in 2.4m, 2.7m and 3.0m lengths in galvanised material only.

Perforated Thin Coat Bead is used to reinforce and protect one-coat finish of plaster on corners and reveals at its weakest points on internal walls and plasterboard.

Two profiles are available - Standard range with a 22mm flange and Premier range with a 24mm flange both with a 79.5 degree angle.

A 135 degree bead is also available with a 24mm wing for unusual corners.

#### Specification

All galvanised materials are manufactured from steel to DX51.BSEN 10142 (g 275).

Manufactured in accordance with BS6452 Part 1: 1984.



Standard



Premier

Perforated Thin Coat Bead is available in boxes of 50 lengths per carton.

Code	Material	Length (m)	Size (mm)
GPTCB24	Galvanised Steel	2.4	22 x 22
GPTCB27	Galvanised Steel	2.7	22 x 22
GPTCB30	Galvanised Steel	3.0	22 x 22
GPPTCB24	Galvanised Steel	2.4	24 x 24
GPPTCB27	Galvanised Steel	2.7	24 x 24
GPPTCB30	Galvanised Steel	3.0	24 x 24
GTCB13530	Galvanised Steel	3.0	24 x 24 (135° wing)